

# Mini loader tyres for hard, abrasive surfaces

## MICHELIN XZSL

Radial construction



RESISTANCE  
LONGEVITY  
COMFORT

Mini loaders



Backhoe loaders



### Sizes

335/80 R18 TL 151A2/139B  
335/80 R20 TL 153A2/141B  
375/75 R20 TL 155A2/143B  
405/70 R20 TL 155A2/143B  
425/75 R20 TL 167A2/155B



## ■ Excellent resistance to damage

- Assured machine availability through less downtime, fewer punctures or perforations thanks to its chunky tread, a steel reinforced crown, robust shoulders and protected sidewalls.

## ■ Exceptional machine output

- A very long service life due to better protection against impacts and abrasions, thanks to a deep tread pattern, large shoulder blocks, a continuous central tread band and optimised rubber compounds.

## ■ Increased productivity

- The certainty that your machine will go almost anywhere,
- Exceptional mobility thanks to a deep, non-directional tread and offset blocks on the shoulders and sidewalls.

# Characteristics of Compact Line radial tyres

## MICHELIN XZSL

Ø inches	Tyre sizes	CAI	Tyre characteristics				Rim widths <sup>(1)</sup> inches	Tube <sup>(2)</sup>	75% internal volume litres
			S mm	D mm	R' mm	R.C mm			
<b>18</b>	335/80 R18 151A2/139B TL XZSL  (12.,5 R18)	122999	337	995	455	3020	<b>11</b>  W10, 11SDC	828	105
<b>20</b>	335/80 R20 153A2/141B TL XZSL  (12.5 R20)	792581	337	1068	487	3235	<b>11</b>  W10, 11SDC	444	110
	375/75 R20 155A2/143B TL XZSL  (14.5 R20)	122989	395	1067	489	3241	<b>11</b>	664	122
	405/70 R20 155A2/143B TL XZSL  (16.0/70 R20)	753584	418	1103	504	3314	<b>13</b>  11, 11SDC, 12, 12SDC, 13SDC	664	150
	425/75 R20 167A2/155B TL XZSL  (16.5/75 R20)	122979	434	1142	510	3439	<b>13</b>  11, 11SDC, 13SDC, 12	829	180

<sup>(1)</sup> The reference rim is shown in bold type.

<sup>(2)</sup> KLEBER tube code.

### Pressure (bar) and (psi) – Load per tyre in kg

	Bar Psi	1.00 15	1.20 17	1.40 20	1.60 23	1.80 26	2.00 29	2.20 32	2.40 35	2.60 38	2.80 41	3.00 44	3.20 46	3.40 49	3.60 52	3.80 55
Stat		2 415	2 635	2 860	3 080	3 300	3 525	3 745	3 970	4 190	4 410	4 635	4 855	5 075	5 300	5 520
10		1 510	1 650	1 785	1 925	2 065	2 205	2 340	2 480	2 620	2 755	2 895	3 035	3 175	3 310	3 450
25		1 240	1 355	1 470	1 585	1 700	1 815	1 930	2 040	2 155	2 270	2 385	2 500	2 615	2 730	2 845
30		1 210	1 320	1 430	1 540	1 655	1 765	1 875	1 985	2 095	2 205	2 315	2 430	2 540	2 650	2 760
40		1 090	1 190	1 290	1 395	1 495	1 595	1 695	1 800	1 900	2 000	2 100	2 200	2 305	2 405	2 505
50		1 060	1 160	1 255	1 355	1 450	1 550	1 645	1 745	1 845	1 940	2 040	2 135	2 235	2 330	2 430
Stat		2 560	2 795	3 030	3 265	3 495	3 730	3 965	4 200	4 435	4 670	4 905	5 135	5 370	5 605	5 840
10		1 600	1 745	1 895	2 040	2 185	2 330	2 480	2 625	2 770	2 920	3 065	3 210	3 355	3 505	3 650
25		1 320	1 440	1 565	1 685	1 805	1 925	2 050	2 170	2 290	2 415	2 535	2 655	2 775	2 900	3 020
30		1 280	1 395	1 515	1 630	1 750	1 865	1 985	2 100	2 215	2 335	2 450	2 570	2 685	2 805	2 920
40		1 165	1 270	1 380	1 485	1 590	1 695	1 805	1 910	2 015	2 125	2 230	2 335	2 440	2 550	2 655
50		1 130	1 235	1 335	1 440	1 545	1 650	1 750	1 855	1 960	2 060	2 165	2 270	2 375	2 475	2 580
Stat		2 720	2 970	3 220	3 470	3 715	3 965	4 215	4 465	4 715	4 965	5 215	5 460	5 710	5 960	6 210
10		1 700	1 855	2 010	2 165	2 325	2 480	2 635	2 790	2 945	3 100	3 255	3 415	3 570	3 725	3 880
25		1 390	1 520	1 650	1 775	1 905	2 035	2 165	2 290	2 420	2 550	2 680	2 810	2 935	3 065	3 195
30		1 360	1 485	1 610	1 735	1 855	1 980	2 105	2 230	2 355	2 480	2 605	2 725	2 850	2 975	3 100
40		1 225	1 340	1 450	1 565	1 680	1 790	1 905	2 020	2 130	2 245	2 355	2 470	2 585	2 695	2 810
50		1 190	1 300	1 410	1 520	1 630	1 740	1 850	1 960	2 070	2 180	2 290	2 400	2 510	2 620	2 730
Stat		2 720	2 970	3 220	3 470	3 715	3 965	4 215	4 465	4 715	4 965	5 215	5 460	5 710	5 960	6 210
10		1 700	1 855	2 010	2 165	2 325	2 480	2 635	2 790	2 945	3 100	3 255	3 415	3 570	3 725	3 880
25		1 390	1 520	1 650	1 775	1 905	2 035	2 165	2 290	2 420	2 550	2 680	2 810	2 935	3 065	3 195
30		1 360	1 485	1 610	1 735	1 855	1 980	2 105	2 230	2 355	2 480	2 605	2 725	2 850	2 975	3 100
40		1 225	1 340	1 450	1 565	1 680	1 790	1 905	2 020	2 130	2 245	2 355	2 470	2 585	2 695	2 810
50		1 190	1 300	1 410	1 520	1 630	1 740	1 850	1 960	2 070	2 180	2 290	2 400	2 510	2 620	2 730
Stat		3 825	4 175	4 525	4 875	5 225	5 575	5 925	6 270	6 620	6 970	7 320	7 670	8 020	8 370	8 720
10		2 390	2 610	2 825	3 045	3 265	3 485	3 700	3 920	4 140	4 355	4 575	4 795	5 015	5 230	5 450
25		1 990	2 170	2 355	2 535	2 720	2 900	3 085	3 265	3 445	3 630	3 810	3 995	4 175	4 360	4 540
30		1 910	2 085	2 260	2 435	2 610	2 785	2 960	3 135	3 310	3 485	3 660	3 835	4 010	4 185	4 360
40		1 750	1 910	2 070	2 230	2 390	2 550	2 710	2 870	3 035	3 195	3 355	3 515	3 675	3 835	3 995
50		1 700	1 855	2 010	2 165	2 325	2 480	2 635	2 790	2 945	3 100	3 255	3 415	3 570	3 725	3 880

Stat : Static load at 0 km/h, stationary vehicle.

10 : Maximum speed 10 km/h without high and sustained torque.

25 : Use under torque and travel on the road at up to 25 km/h.

30 : Use under torque and travel on the road at up to 30 km/h.

40 : Use on the road at up to 40 km/h

50 : Use on the road at up to 50 km/h.

**IMPORTANT :** The inflation pressure is always determined according to the load per tyre, the speed of travel and the work to be done