



RESILIENT | **ORCA**

BALANCED PERFORMANCE

PERFORMANCE DEFINED

TIRE LIFE



Trelleborg products guarantee **the best wear** performance in the industry. This results in longer tire life, **additional hours of usage**, reduced downtime and lower maintenance costs.

ENERGY SAVING



Trelleborg is the **largest approved tire manufacturer to the OEMs**. We work closely with them to ensure we meet the requirements of energy consumption. This results in **reduced fuel costs** for our customers.

STABILITY



Trelleborg products are designed to have **large footprints** giving a maximum contact area leading to better stability and even tire wear.

COMFORT



Trelleborg understands the requirements of a **safe working environment**. Our products are designed to reduce vibration and **keep noise to a minimum level**. We follow the strictest regulations for work safety while providing a comfortable ride.

PERFORMANCE AGAINST COMPETITOR

TIRE LIFE



ENERGY SAVING



STABILITY



COMFORT




ORCA

Orca is designed with one objective: performance at a competitive price.

For applications that are not in constant use or that carry a lower load as standard Orca proves itself as the most cost effective tire in its class. Long mileage, low energy consumption and excellent cut resistance all mean that Orca delivers a solid performance for a lower investment

Orca tires are available in the most common sizes in both LOC and NON LOC (nose retaining bead for easy mounting) and in Non Marking Grey compound.



Orca

Counterbalanced Forklift Truck:
load capacity up to 25 km/h

Tire Size	Rim	Pattern	LOC Version	Width [mm]	Overall Diameter [mm]	Load Wheels [kg]	Steer Wheels [kg]	Other Vehicles: load capacity @ 10 km/h [kg]
4.00-8	3.00D-8	Orca	Yes	94	398	950	730	865
15x4½-8	3.00D-8	Orca	Yes	110	373	1040	800	945
5.00-8	3.00D-8	Orca	Yes	114	452	1420	1090	1290
16x6-8	4.33R-8	Orca	Yes	143	409	1495	1150	1360
18x7-8	4.33R-8	Orca	Yes	147	445	2145	1650	1950
140/55-9	4.00E-9	Orca	Yes	132	380	1170	900	1065
6.00-9	4.00E-9	Orca	Yes	130	520	1885	1450	1715
21x8-9	6.00E-9	Orca	Yes	180	514	2760	2120	2505
6.50-10	5.00F-10	Orca	Yes	153	568	2340	1800	2125
200/50-10	6.50F-10	Orca	Yes	175	450	2470	1900	2245
23x9-10	6.50F-10	Orca	Yes	187	574	3445	2650	3130
7.00-12	5.00S-12	Orca	Yes	163	646	2915	2240	2645
23x10-12	8.00G-12	Orca	Yes	219	570	3770	2900	3425
27x10-12	8.00G-12	Orca	Yes	235	670	3900	3000	3540
7.00-15	5.5-15	Orca	Yes	162	717	3545	2725	3220
28x9-15	7.0-15	Orca	Yes	200	680	3900	3000	3540
7.50-15	6.5-15	Orca	Yes	186	743	3900	3000	3540
250-15	7.0-15	Orca	Yes	206	709	4745	3650	4310
250-15	7.5-15	Orca	Yes	206	709	4745	3650	4310
8.25-15	6.5-15	Orca	Yes	192	803	4745	3650	4310
300-15	8.0-15	Orca	Yes	244	807	5850	4500	5310
355/65-15	9.75-15	Orca	Yes	260	809	7800	6000	7080

*In accordance to ETRTO Standard

AVAILABLE ADDITIONAL COMPOUNDS

NM

NON MARKING