



ELS2 (E4 INDUSTRIAL)

E-LUG S2







The E-LUG S2 bias tire is specially designed for reach stackers, top picks, straddle carriers, and other container handling equipment.

Designed for container handler applications
Strong resistance to puncture and sidewall damage
Industrial application compound and construction

CATEGORY	TIRE SIZE	ARTICLE	PLY RATING	COMPOUND	TRA	AVERAGE WEIGHT	<u> (32ND)</u>	RIM/ FLANGE	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	STATIC LOAD Radius	STATIC Loaded Width	MIN DUAL Spacing	REVS PER MILE
Small Tubeless	18.00-25	422894	40	IDU	E-4	810	84	13.00/2.5	66.3	20.3	31.3	20.9	23.1	310
Large Tubeless	18.00-33	423645	36	IDU	E-4	960	84	13.00/2.5	73.2	20.0	34.9	21.0	23.1	280
	21.00-35	423653	40	IDU	E-4	1,300	84	15.00/3.0	80.3	23.3	37.6	24.3	27.6	257

Equipment icons shown on this bulletin denote general categories, not specific tire applications.

ELS2

E-LUG S2

(E4 INDUSTRIAL)