

**BRIDGESTONE**



**RL**  
**(E3/L3 INDUSTRIAL)**

R-LUG



OFF-THE-ROAD TIRES



The R-LUG bias tire is specially designed for reach stackers, top picks, straddle carriers, and other container handling equipment.

- ✓ *Non-directional tread pattern for outstanding wear resistance*
- ✓ *Special compounds to resist heat*
- ✓ *Exceptional cut resistance*

CATEGORY	TIRE SIZE	ARTICLE	PLY RATING	COMPOUND	TRA	AVERAGE WEIGHT	OTD (32ND)	RIM/ FLANGE	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	STATIC LOAD RADIUS	STATIC LOADED WIDTH	MIN DUAL SPACING	REVS PER MILE
Small Tube Type	10.00-20	175625	16	IDU	E3/L3	130	28	7.50V	42.0	11.2	19.8	11.3	13.1	490
	12.00-20	181099	20	IDU	E-3	180	32	8.50V	44.8	12.4	21.1	13.0	15.1	459
	14.00-24	153532	28	IDU	L-3	300	35	10.00VA	53.3	14.4	24.7	15.7	17.7	388
Small Tubeless	14.00-24	153818	24	IDU	L-3	280	35	10.00VA	53.3	15.2	24.2	16.1	17.7	390
	21.00-25	424789	40	IDU	L-3	1,010	52	15.00/3.0	68.7	22.8	30.5	24.4	26.3	305

Equipment icons shown on this bulletin denote general categories, not specific tire applications.