

BRIDGESTONE



VMTS

(E4)

V-STEEL M-TRACTION S





The V-STEEL M-TRACTION S radial tire features a deep traction design with heat and cut resistant tread compounds.

- ✓ *Non-directional tread design ideal for muddy or soft surfaces*
- ✓ *Exceptional side-slip resistance*
- ✓ *Wear resistance for longer tread life*

CATEGORY	TIRE SIZE	ARTICLE	PLY RATING	COMPOUND	TRA	AVERAGE WEIGHT	OTD (32ND)	RIM/ FLANGE	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	STATIC LOAD RADIUS	STATIC LOADED WIDTH	MIN DUAL SPACING	REVS PER MILE
Small Tube Type	14.00R24	153443	3*	E2A LS	E-4	420	48	10.00W	55.1	15.2	25.3	16.9	17.7	381
Small Tubeless	14.00R25	295213	3*	E3A	E-4	390	48	10.00/1.5	55.4	15.3	25.6	17.1	17.7	379
	16.00R25	422347	2*	E2A	E-4	580	57	11.25/2.0	60.4	17.7	27.4	20.0	20.2	348
	18.00R25	418269	2*	E1A	E-4	800	64	13.00/2.5	64.9	20.2	29.7	22.5	23.1	324
	18.00R25	418323	2*	E2A	E-4	800	64	13.00/2.5	64.9	20.2	29.7	22.5	23.1	324
Large Tubeless	18.00R33	418277	2*	E1A	E-4	920	64	13.00/2.5	73.3	20.3	33.4	22.7	23.1	287
	18.00R33	418331	2*	E2A	E-4	920	64	13.00/2.5	73.3	20.3	33.4	22.7	23.1	287
	18.00R33	422320	2*	E2A LS	E-4	920	64	13.00/2.5	73.3	20.3	33.4	22.7	23.1	287
	21.00R35	418285	2*	E1A	E-4	1,290	68	15.00/3.0	80.2	22.6	36.7	25.8	27.6	262
	21.00R35	418358	2*	E2A	E-4	1,290	68	15.00/3.0	80.2	22.6	36.7	25.8	27.6	262
	24.00R35	418293	2*	E1A	E-4	1,720	74	17.00/3.5	85.6	26.0	38.6	28.9	31.3	245
	24.00R35	418366	2*	E2A	E-4	1,720	74	17.00/3.5	85.6	26.0	38.6	28.9	31.3	245
Giant Tubeless	24.00R49	418307	2*	E1A	E-4	2,220	74	17.00/3.5	99.6	25.8	45.9	28.9	35.1	211
	24.00R49	418374	2*	E2A	E-4	2,220	74	17.00/3.5	99.6	25.8	45.9	28.9	31.3	211
	27.00R49	418315	2*	E1A	E-4	2,860	81	19.50/4.0	105.9	29.5	48.4	32.9	35.1	198
	27.00R49	418382	2*	E2A	E-4	2,860	81	19.50/4.0	105.9	29.5	48.4	32.9	35.1	198
	27.00R49	419524	2*	E2A LS	E-4	2,860	81	19.50/4.0	105.9	29.5	48.4	32.9	35.1	198
	27.00R49	418447	2*	E3A	E-4	2,880	81	19.50/4.0	105.9	29.5	48.4	32.9	35.1	198