

BRIDGESTONE



VMT
(E3, L3)

V-STEEL M-TRACTION



OFF-THE-ROAD TIRES



The V-STEEL M-TRACTION premium radial tire provides excellent traction in heavy-duty wheel loader, earthmover and articulated dump truck applications.

- ✓ *Non-directional tread pattern for even wear*
- ✓ *Cool running, heat resistant compound*
- ✓ *Excellent traction in a variety of conditions*

CATEGORY	TIRE SIZE	ARTICLE	PLY RATING	COMPOUND	TRA	AVERAGE WEIGHT	OTD (32ND)	RIM/ FLANGE	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	STATIC LOAD RADIUS	STATIC LOADED WIDTH	MIN DUAL SPACING	REVS PER MILE
Small Tubeless	17.5R25	419346	1*	D2A	L-3	380	38	14.00/1.5	53.4	17.3	23.6	20.2		393
	20.5R25	418110	1*	D2A	L-3	510	42	17.00/2.0	58.3	20.9	25.7	23.5		360
	20.5R25	418161	2*	E1A	E-3	520	42	17.00/2.0	58.3	20.9	25.7	23.5		360
	23.5R25	418137	1*	D2A	L-3	750	44	19.50/2.5	63.0	24.3	27.6	27.1		333
	23.5R25	418196	2*	E1A	E-3	710	44	19.50/2.5	63.0	24.3	27.6	27.1		333
	23.5R25	418773	2*	E2A	E-3	720	44	19.50/2.5	63.0	24.3	27.6	27.1		333
Large Tubeless	26.5R25	419672	1*	D2A	L-3	980	48	22.00/3.0	68.5	26.9	29.7	30.2		307
	26.5R25	419311	2*	E1A	E-3	910	48	22.00/3.0	68.5	26.9	29.7	30.2		307
	29.5R25	419680	1*	D2A	L-3	1,310	53	25.00/3.5	73.4	30.0	31.8	34.2		286
	29.5R25	419338	2*	E1A	E-3	1,310	53	25.00/3.5	73.4	30.0	31.8	34.2		286
Giant Tubeless	30.00R51	422207	2*	E3A	E-3	3,450	57	22.00/4.5	112.2	33.6	50.9	37.4	39.1	187
	33.00R51	422436	2*	E1A	E-3	4,100	61	24.00/5.0	117.6	36.7	52.7	41.4	42.3	179
	33.00R51	420689	2*	E3A	E-3	4,410	61	24.00/5.0	117.6	36.7	52.7	41.4	42.3	179
	36.00R51	421871	2*	E1A	E-3	4,890	66	26.00/5.0	123.9	40.0	55.2	45.4	46.6	170
	36.00R51	010316	2*	E3A	E-3	4,910	66	26.00/5.0	123.9	40.0	55.2	45.4	46.6	170
	40.00R57	427016	2*	E1A	E-3	6,970	81	29.00/6.0	138.3	43.6	61.4	49.8	53.6	152
	40.00R57	427050	2*	E2A	E-3	6,970	81	29.00/6.0	138.3	43.6	61.4	49.8	53.6	152
	40.00R57	427033	2*	E3A	E-3	6,970	81	29.00/6.0	138.3	43.6	61.4	49.8	53.6	152