

**MICHELIN® X-STRADDLE® 2**  
**480/95 R 25**

**MOVING CONTAINERS**  
**FURTHER AND FASTER<sup>(1)</sup>**



**RUN FURTHER<sup>(7)</sup>**

**EXTENDED TIRE LIFE MEANS LESS STOPS**  
**FOR MORE PRODUCTIVITY**


**+8% TREAD VOLUME<sup>(1)</sup>**



**NARROWER LONGITUDINAL GROVES MEANS LESS EXPOSED PLYS**  
**AND GREATER RESISTANCE TO CROWN AGGRESSION**



MICHELIN® X-STRADDLE®




MICHELIN® X-STRADDLE® 2

**EXTENDED BEAD AREA DURABILITY<sup>(1)</sup>**

**30% larger<sup>(1)</sup> bead wire**

**Thicker bead and sidewall profile<sup>(1)</sup>**



**UP TO**  
**+15%**  
**TIRE LIFE<sup>(7)</sup>**

MICHELIN® X-STRADDLE® 2 480/95 R 25 TL 206 A7 CAI 653072

(1) Compared to MICHELIN® X-STRADDLE® 480/95 R 25

(7) Compared to MICHELIN® X-STRADDLE® 480/95 R 25, average performance by port site. Projected improvement in tire life based on field performance in customer port sites of the MICHELIN® X-STRADDLE® 2 450/95R25 size compared to the MICHELIN® X-STRADDLE® 16.00R25 (the 450/95R25 is an equivalent size of the 16.00R25), that included individual design improvements incorporated into the MICHELIN® X-STRADDLE® 2 480/95R25.



More information: [www.michelinearthmover.com](http://www.michelinearthmover.com)  
Michelin Earthmover Youtube

**MICHELIN® X-STRADDLE® 2**  
**MOVING CONTAINERS**  
**FURTHER AND FASTER<sup>(1)</sup>**



Get more productivity  
for your twin lift operations:  
further, faster with  
no compromise  
on safety<sup>(1)</sup>.



(1) Compared to MICHELIN® X-STRADDLE® 480/95 R 25





**YOUR STAKES**  
 "I EXPECT TIRES TO BE SAFE FOR MY DRIVERS, TO CONTRIBUTE TO MEETING MY PRODUCTIVITY CHALLENGES WHILE KEEPING MY COSTS UNDER CONTROL."

**GET MORE PRODUCTIVITY FOR YOUR TWIN LIFT OPERATIONS: FURTHER, FASTER WITH NO COMPROMISE ON SAFETY<sup>(1)</sup>.**



**HIGH LOAD CAPACITY**

**MORE AIR INSIDE MEANS MORE LOAD CAPACITY**

The MICHELIN® X-STRADDLE® 2 480/95 R 25 tire has **+20%** more air volume than MICHELIN® X-STRADDLE® 2 450/95 R 25



MICHELIN® X-STRADDLE® 2 450/95 R 25  
 MICHELIN® X-STRADDLE® 2 480/95 R 25

The highest load capacity of the straddle carrier tire market **between 15 and 22km/h<sup>(2)</sup>**

**+**  
**Carry up to 17.85 Tons<sup>(3)</sup>**



**RUN FASTER<sup>(4)</sup>**

A faster running tire thanks to improved heat dissipation



**MICHELIN® X-STRADDLE® 480/95 R 25**

**12KM DISTANCE PER HOUR**

and 30km/h max speed

**MICHELIN® X-STRADDLE® 2 480/95 R 25**

**15KM DISTANCE PER HOUR**

and 35km/h max speed

**+25%<sup>(4)</sup>**  
**OF DISTANCE PER HOUR**



**SIMPLICITY**

The MICHELIN® X-STRADDLE® 2 480/95 R 25 should be mounted on **13.00/2.5** recommended rim<sup>(5)</sup> and can also be fitted on **11.25/2.0** rim<sup>(6)</sup>



(1) Compared to MICHELIN® X-STRADDLE® 480/95 R 25

(2) At the nominal pressure of 10 bars, vs 15.75 Tons for MICHELIN X-STRADDLE® 2 450/95 R 25. And carry 17 Tons from 22km/h to 25km/h

(3) Data gathered from Bridgestone "off-the-road tires for industrial use" e-brochure (July2016), Goodyear "container handling tyres and industrial use" e-brochure (July2016)

(4) MICHELIN® X-STRADDLE® 2 480/95R25 max distance of 15 kilometers in one hour and 35 km/h max speed vs MICHELIN® X-STRADDLE® 480/95R25 : max distance of 12 kilometers in one hour and 30 km/h max speed

(5) 13.00/2.5 measuring rim - Rim width : 13.00" Flange height : 2,5"

(6) 11.25/2.0 approved rim - Rim width : 11.25" Flange height : 2,0"